

Technical specifications Bulletin Board

| | | | |
|---|---|--------------|--|
|  | Total Thickness | EN-ISO 24346 | 6.0 mm ± 0.25 mm |
|  | Roll Width | EN-ISO 24341 | 1.22 m (3 colours in 1.83 m) |
|  | Roll Length | EN-ISO 24341 | ≤ 28 m |
|  | Total Weight | EN-ISO 23997 | 4.7 kg/m ² ± 10% |
|  | Flexibility | EN-ISO 24344 | Ø 50 mm, according to method A |
|  | Sound absorption coefficient | EN-ISO 354 | α _w 0.1 (typical) |
|  | Thermal conductivity | EN 12524 | 0.10 W/m-K |
| | Self-healing properties | LH000420 | yes |
| | Force on pins - Perpendicular to pin direct | LH000421 | 25 N (typical) |
| | Force on pins - Perpendicular to pin at 7 mm | LH000421 | 10 N (typical) |
| | Force on pins - Parallel to pin (pulling the pin out) | LH000421 | 15 N (typical) |
|  | Bacteriostatic properties | EN-ISO 22196 | yes |
|  | Chemical resistance | EN-ISO 26987 | Resistant to diluted acids, oils and the most conventional solvents such as alcohol, white spirit, etc. Not resistant to prolonged exposure to alkalis. |
|  | Dimension stability | | Due to the natural jute back, providing a strong durable foundation, the product is dimensionally stable in all directions when properly installed. It resists cracking, drying and peeling. |
| | Anti-static | | yes |
| | Gloss | | Only available in matt colors, so that reflection caused by sunlight or artificial light is reduced. |
| | Natural materials (e.g. cork, linseed oil, jute) | | 91% |
| | Recycled content | | 43% |
| | PVC, PET, plasticizers content | | 0% |

All Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

