

Cleaning & Maintaining

Product: Sonus AluBeam

1. For cleaning, a soft and damp cloth can be used. No cleaning liquid should be used in temperatures over 104°f. This can cause permanent plaque deposits to form over the paint.
2. The surface should not be cleaned with cleaning materials that contain alcohol and ammonia.
3. Products that are exposed to sunlight can fade away in time. In order to prevent this, it is recommended to renew the varnishing at least every 5 years with water based varnish. This duration might be longer or shorter depending on the exposure to sunlight.
 - a. Before varnish treatment, it is essential that the surface is deprived from all kinds of foreign materials, oils, old paint residue, silicon and dust. A foam/sponge or 220 grit sandpaper can be used to do this.
 - b. With the help of a roller or brush, 2 or 3 coats of varnish is applied to the surface that is free of dust. The instruction given by the varnish producer should be complied with.
 - c. Ideal application temperature is between 60° and 85°f. It is not recommended to be applied in temperatures below 50°f.
 - d. The relative humidity during the application should be below 80%. For maintenance, spring or summer months are preferred.
 - e. Please adhere to all warnings and instructions from the Varnish manufacturer and ensure proper safety precautions are followed while applying varnish.

Guidance:

- Always apply any cleaning methods to a small area first to test effectiveness and result.
- Always use a minimal amount of cleaning solution and use a damp cloth to remove any excess soap or cleaning solution; otherwise, it will collect dust and dirt.
- It is not necessary to remove the panel to perform any face cleaning. Just make sure you hold the panel in place while cleaning to prevent any potential loosening of the mounting hardware.
- When in doubt...don't!