



Product Specifications: Carta Smooth (Non-Vinyl Wallcovering)

Product	PVC-Free Durable Smooth Wall Paper Manufactured by HP
---------	--

Physical Properties	DESCRIPTION Type II, 17 mil Eco-Friendly PVC-Free Wallcovering CONSTRUCTION Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks
---------------------	--

SUBSTRATE

Roll Width 54" (1.37 m)
Weight 290 g/m² per TAPPI T-410 Test Method
Face Latex-Saturated Wet-Strength Paper
Backing Textile Scrim

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke	ASTM-E84 Class A Fire Rated Compliant with California Fire Code CA 1237 Compliant with IBC (International Building Code) sec. 803.1.1
---------------	---

Mold and Mildew	Highly Resistant – GREENGUARD Test method, GGTM.P040 per guidelines of ASTM D6329
-----------------	---

Specifications	EN233 – Spongeability rating (wave 1), Excellent color fastness rating Carries the CE certification according to European Standard EN15102.
----------------	--

Environmental	REACH compliant FSC®-certified paper Compliant with CHPS Section 01350
---------------	--



(440) 248-0000

6655 parkland blvd
solon, ohio 44139
surfacematerials.com

v0226