



Product Specifications: PNS Permanent Self-Adhesive Vinyl

Product

MacTac Poodle
Manufactured by MacTac

Physical Properties

DESCRIPTIONMatte White, Semi-Rigid Calendared PVC Vinyl
CONSTRUCTIONPermanent acrylic pressure sensitive PVC vinyl with UV-LED inks
SUBSTRATE
Roll Width54"
Weight6.0 mil
Liner72# P.E. Coated Kraft Liner
INKS
UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers.
UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

Flame & Smoke

SUBSTRATE
ASTM E84 Class A
ANSI/NFPA 255 Class A
IFC 8-1 Class A
Flame Spread..... 20
Smoke Developed 160

Durability

Temperature Range
Minimum Application: 50°F (10°C)
End Use: -40°F to 180°F (-40°C to 82°C)
Peel Adhesion lb./in.
Property: (N/25 mm) 180° on Stainless Steel - 24 hr.
Typical Values: 5.3 (23.2)
Test Method: ASTM D-903
Dimensional Stability, inches (mm)
48 hours @ 158°F
MD, 0.20
CD, 0.10
Shelf Life
2 years from Date of Manufacturer when store at 60 60/77°F (15/25°C) and 50% relative humidity in the original package.