

Spartina[™]

52" / Type II FBV Mylar[®] / 20 oz.

This pattern is constructed with Mylar and has special installations instructions.

Please visit Denovowall.com for more information prior to installation.

Low VOC 01350 compliant

Physical Properties:

Total Weight	U.S. Units	Metric Units
	20.0 oz./LY	619 G/PLM
	13.3 oz./SQ	451 G/PSM
Fabric Type	Osnaburg	
Material Width	52"	132 cm
Repeat	Horizontal 52" x Vertical 18"	

Federal Specifications:

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results:

ASTM E-84 Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 60
 Passes NFPA 286 Corner Burn Test

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

INSTALLATION NOTE
Spartina[™] is a straight hang / random match
 For specifications and hanging instructions go to: www.denovowall.com