



**surface**materials

*The ultimate in interior finish products.*

**(440) 248-0000**

6655 parkland boulevard  
solon, ohio 44139  
(440) 519-1950 fax  
www.surfacematerials.com

### Environmental sustainable, Acoustical Wallcovering

A socially responsible, eco-friendly wallcovering engineered from 100% solution dyed fibers, with *recycled* content, needled into a continuous structure, then finished with a heatset, latex back to ensure fiber lock. This material is soft, flexible and acoustically absorbent, yet suitable for high-traffic areas. Its "self-healing" nature makes it ideal for Tackable walls while its excellent pill/fuzz resistance makes it Velcro compatible.

## Specifications

Construction:	Needlebond
Pattern:	Single Rib
Fiber:	Post Industrial; Polyester/Polypropylene Blend
Total Weight:	30.0 oz. Ln. yd.
Roll Size (W x L):	54" x 24 Ln. yd. (w x l)
Packaging:	"Crush-Proof" Box

## Properties

### Performance/Test Method

#### Flammability

NFPA - 265	Passes
UBC 8-2 Corner Burn	Passes
ASTM E-84 Tunnel Test	Class A
Sec. X 1.10.1	

#### Acoustical

ASTM C-423-84A	
Gypsum Board	NRC .20
Acoustic Board	NRC .60

#### Colorfast

AATCC-165	
Wet Crocking	5; No Stain
Dry Crocking	4-5; Slight Stain

#### Electrostatic

AATCC-134	0.2 kv
-----------	--------

#### Durability

ASTM D-3884	10,000 CYCLES to Rupture
-------------	--------------------------

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT FURNISHED HEREUNDER OTHER THAN AT THE TIME OF DELIVERY IT SHALL BE OF THE QUALITY AND SPECIFICATION STATED HEREIN. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED, AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE, ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. ANY RECOMMENDATIONS MADE BY THE SELLER CONCERNING THE USES OR APPLICATIONS OF SAID PRODUCT ARE BELIEVED RELIABLE AND SELLER MAKES NO WARRANTY OF RESULTS TO BE OBTAINED. IF THE PRODUCT DOES NOT MEET CROSSPOINT'S CURRENT PUBLISHED SPECIFICATIONS, AND THE CUSTOMER GIVES NOTICE TO CROSSPOINT FABRICS BEFORE INSTALLING THE PRODUCT, CROSSPOINT FABRICS WILL REPLACE THE PRODUCT WITHOUT CHARGE OR REFUND THE PURCHASE PRICE.



**surface**materials

*The ultimate in interior finish products.*

**(440) 248-0000**

6655 parkland boulevard  
solon, ohio 44139  
(440) 519-1950 fax  
www.surfacematerials.com

## Acoustical Wallcovering Adhesives

### 1. General:

- ▶ Recommendations of wallcovering adhesive manufacturer should be strictly followed and take precedence.
- ▶ Apply premixed, undiluted, heavy-duty wallcovering adhesive to the wall-NOT THE FABRIC.
- ▶ Allow adhesive to become tacky, not dry.
- ▶ A clear, non-staining adhesive will -help prevent problems if dropped on the face of the material.
- ▶ If adhesive lands on the face of the material, check with adhesive manufacturer.

### 2. Recommendations:

- ▶ Shur-stik 111                      Gibson-Homans, Twinsburg,OH
- ▶ Pro 838                              Roman Adhesives, Calumet,IL

The above recommended adhesives are appropriate based upon practical field experience and in no way, expressed or implied, are meant to be a warranty. Contact the adhesive supplier or manufacturer for final recommendations for type and application methods.

For best results, it is recommended that a qualified textile wallcovering installer be employed.



**surface**materials

*The ultimate in interior finish products.*

**(440) 248-0000**

6655 parkland boulevard  
solon, ohio 44139  
(440) 519-1950 fax  
www.surfacematerials.com

## **Acoustical Wallcovering Installation**

### **1. Preparation:**

- ▶ Remove all wall plates, obstructions and old wallcovering.
- ▶ Clean, seal and prime wall before application, especially glossy and semi-gloss paint, wood or concrete walls.
- ▶ Seal markings that cannot be removed by cleaning to prevent "bleed-thru".
- ▶ Carefully inspect all material before installation.
- ▶ Ensure pattern and color is satisfactory and meet specification.

### **2. Adhesive Application:**

- ▶ Recommendations of adhesive manufacturer should be strictly followed and take precedence.
- ▶ Apply premixed, undiluted, heavy-duty, clear wallcovering adhesive to the wall-NOT THE FABRIC.
- ▶ Allow adhesive to become tacky, not dry.
- ▶ A clear, non-staining adhesive will help prevent problems if dropped on the face of the material.
- ▶ Care should be taken not to get adhesive on the face. If necessary, check with adhesive manufacturer.

### **3. Installation:**

- ▶ For best results, install rolls in numerical sequence by dye lot.
- ▶ Cut material to desired lengths; allow minimum 2" on the top and bottom for trimming.
- ▶ After cutting, installer or distributor assumes all responsibility.
- ▶ Acoustical wallcoverings have a knap. Check every roll and cut for knap direction prior to installation. **DO NOT ASSUME KNAP DIRECTION IS THE SAME ON ALL ROLLS. DO NOT REVERSE STRIPS;** they may appear as a different color or shade.
- ▶ Install 3 strips in sequence with knap in same direction.
- ▶ Inspect for color, pattern, uniformity and application. If acceptable, proceed with work.
- ▶ Continue to inspect in 3 strip intervals. If unacceptable-**STOP WORK IMMEDIATELY.** Contact your local representative.
- ▶ All edges are trimmed to a rib, butt seamed and steel rolled - **DO NOT DOUBLE CUT.**
- ▶ This product is not precision trimmed. Trim on a table, in the same "groove", using a straight edge to insure an accurate cut.
- ▶ To insure a good, clean trim, a new blade should be used on each strip.

The above is based upon practical field experience and in no way, expressed or implied, is meant to be a warranty. No claims are allowed for labor. All returns must be made with prior Return Authorization Number, subject to a 30% restocking fee and completed within 30 days of shipping.

For best results, it is recommended that a qualified textile wallcovering installer be employed.