

<b>STYLE:</b>	Tiara II	
<b>STYLE NUMBER:</b>	251CR	
<b>CONSTRUCTION:</b>	Needlebond	
<b>PATTERN:</b>	Single Rib	
<b>FIBER:</b>	PP/ Recycled Polyester Blend	
<b>TOTAL WEIGHT:</b>	30 oz/ly. (20 oz s/y)	
<b>ROLL SIZE:</b>	54" X 24 Lin. yd.	
<b>PACKAGING:</b>	"Crush-Proof" Box	
<b>FLAMMABILITY:</b>	Passes Corner burn NFPA-265; UBC 8-2 TUNNEL TEST, Class A Rating ASTM E-84	
<b>ACOUSTICAL:</b>	ASTM C-423-84A Gypsum Board NRC .20 Acoustic Board NRC .80	
<b>TENSILE STRENGTH:</b> ASTM D-5034, (LBS)	Break L x W 142 x 132	Elongation L x W 195 x 145
<b>TEAR (TRAP) STRENGTH:</b> ASTM D-2261, (LBS)	L x W 30 x 25	
<b>ABRASION RESISTANCE:</b> ASTM D-3884	Rib # cycles 1,720	Rupture # cycles 2,260
<b>COLOR FAST:</b> AATCC-168	Wet Crocking 5	Dry Crocking 5
<b>FMVSS 302:</b>	Passes	
<b>ELECTROSTATIC:</b> AATCC-134	0.2kv	

The above data may change to reflect industry standards. Please verify with manufacturer.