tapetex by

Churchilllaan 10, 5705 BK Helmond, Holland (+31) 492 534690, info@tapetex.com, tapetex.com

tapetex wall materials

SPECIFICATION : SARAY SILK 65-1310/-1319

Collection : 10 colours from Tapetex-65-Silk/Silky

Physical properties

Surface Composition : 100% Silk; handwoven

Backing : Paper backing of 70% woodpulp reinforced with 30% polyester.

Width : 110 cm = 43"

Weight : Approx. 260 gr/lm = 8.5 oz/lyd

Thickness : Approx. 0.40 mm
Hanging : Random, non-reverse.

Precision trimmed for butt-joining by professional paper hangers.

Installation advice supplied with every roll.

Adhesive : Adhesive Tapetex PRO-1 or similar premixed heavy duty, clear vinyl

adhesive, suitable for textile wallcovering.

Variation : There can be a variation between sample material and finished product.

Stock cuttings are available for approval.

Performance

Surface finish : A stain repellent finish prevents oil and waterbased fluids penetrating

and staining the material.

Periodic vacuuming is recommended to prevent dust from building up on

the materials surface.

Lightfastness : Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest

150S is minimum 5 on the standard blue scale.

Fire rating : ASTM E84 Class A and EUROCLASS B s1 d0

Permeability rating : ASTM E96-12, Method B, Water Vapor Transmission Rate 46

Indoor air quality : Report UL 18369-10 available upon request.

Sustainability

Silk is a 100% renewable natural resource.

The backing is FSC certified, FSC A000531.

In production, all energy sources are either green, wind or hydro based and all processes are waterbased.

The products do not contain PVC, chlorine, plasticizers, heavy metals or harmfull dyes.

Supply and packing

Delivery from stock by the full linear meter or full linear yard.

The average piece length of this quality is approx. 35 linear meter or 38 linear yards. However, as is common within the textile industry, it is not possible to establish a standard roll length.

The wallcovering is reeled on to a cardboard core, wrapped in polyethylene and protective end caps are fixed. Each roll is then packed in individual cardboard boxes or tubes.

Harmonized System as per the World Customs Organization and Origin

Textile Wallcovering, paper backed: 5905.00.

Made in the Netherlands.