

**SPECIFICATION** **FENDA 67-1800/-1809**, a one-layer quality  
Collection 10 colours from Tapetex-67-Nonwoven

### **Physical properties**

Composition	70% FSC certified woodpulp, reinforced with 30% polyester.
Width	137 cm = 54"
Weight	Approx. 220 gr/lm = 7.1 oz/lyd
Thickness	Approx. 0.40 mm
Hanging	Random See Kai 67-1680/1684. Precision trimmed for butt-joining by professional paper hangers. Installation advice supplied with every roll.
Adhesive	Adhesive Tapetex PRO-1 or similar premixed heavy duty, clear vinyl adhesive, suitable for textile wallcovering.
Variation	There can be a variation between sample material and finished product. Stock cuttings are available for approval.

### **Performance**

Surface finish	See detailed results on our website. A stain repellent finish prevents waterbased splashes penetrating and staining the material. Periodic vacuuming is recommended to prevent dust from building up on the materials surface.
Lightfastness	Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.
LRV values	Testing as per BS 8493:2008+A1:2010, Datacolor DC500.
Fire rating	ASTM E84 Class 1 or A and EUROCLASS (B s2 d0).
Permeability rating	Test result 93.8 as per ASTM E96-12, Method B, Water Vapor Transmission.
Indoor air quality	ASTM D6196, D5197 and D5116, Environmental Chamber Test. The testing followed UL 2821 "Greenguard Certification Program Method for Measuring and Evaluating Chemical Emissions".
REACH SVHC	Compliant as per Centexbel testing.
DoP No.	(CPR 305/2011), DOP-CPR-01

### **Sustainability**

The nonwoven is FSC certified, FSC A000531.  
In production, all energy sources are either green, wind or hydro based and all processes are waterbased. The products do not contain PVC, chlorine, plasticizers, heavy metals or harmful dyes.

### **Supply and packing**

Delivery from stock by the full linear meter or full linear yard.  
The average piece length of this quality is approx. 100 linear meter or 110 linear yards. However, as is common within the textile industry, it is not possible to establish a standard roll length.  
The wallcovering is reeled on to a cardboard core, wrapped in polyethylene and protective end caps are fixed. Each roll is then packed in individual cardboard boxes or tubes, which are also made out of FSC certified woodpulp.

### **Harmonized System as per the World Customs Organization and Origin**

Textile Wallcovering, paper backed: 5905.00. Made in the Netherlands.



