

SPECIFICATION	LINO 67-1850/-1859, a one-layer quality
Collection	10 colours from Tapetex-67-Nonwoven
Physical proportion	
Physical properties Composition	70% FSC certified woodpulp, reinforced with 30% polyester.
Width	137  cm = 54''
Weight	
Thickness	Approx. 220 gr/lm = 7.1 oz/lyd Approx. 0.40 mm
	Random
Hanging	
	Precision trimmed for butt-joining by professional paper
	hangers. Installation advice supplied with every roll.
Adhesive	Adhesive Tapetex PRO-1 or similar premixed heavy duty, clear vinyl
	adhesive, suitable for textile wallcovering.
Variation	There can be a variation between sample material and finished product.
	Stock cuttings are available for approval.
Performance	See detailed results on our website.
Surface finish	A stain repellent finish prevents waterbased splashes penetrating
Surface finish	A stain repellent finish prevents waterbased splashes penetrating and staining the material.
Surface finish	
Surface finish	and staining the material.
Surface finish Lightfastness	and staining the material. Periodic vacuuming is recommended to prevent dust from building up
	and staining the material. Periodic vacuuming is recommended to prevent dust from building up on the materials surface.
Lightfastness	and staining the material. Periodic vacuuming is recommended to prevent dust from building up on the materials surface. Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.
Lightfastness LRV values	and staining the material. Periodic vacuuming is recommended to prevent dust from building up on the materials surface. Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest. Testing as per BS 8493:2008+A1:2010, Datacolor DC500.
Lightfastness LRV values Fire rating	and staining the material. Periodic vacuuming is recommended to prevent dust from building up on the materials surface. Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest. Testing as per BS 8493:2008+A1:2010, Datacolor DC500. ASTM E84 Class 1 or A and EUROCLASS (B s2 d0).
Lightfastness LRV values Fire rating	<ul> <li>and staining the material.</li> <li>Periodic vacuuming is recommended to prevent dust from building up on the materials surface.</li> <li>Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.</li> <li>Testing as per BS 8493:2008+A1:2010, Datacolor DC500.</li> <li>ASTM E84 Class 1 or A and EUROCLASS (B s2 d0).</li> <li>Test result 93.8 as per ASTM E96-12, Method B, Water Vapor</li> </ul>
Lightfastness LRV values Fire rating Permeability rating	<ul> <li>and staining the material.</li> <li>Periodic vacuuming is recommended to prevent dust from building up on the materials surface.</li> <li>Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.</li> <li>Testing as per BS 8493:2008+A1:2010, Datacolor DC500.</li> <li>ASTM E84 Class 1 or A and EUROCLASS (B s2 d0).</li> <li>Test result 93.8 as per ASTM E96-12, Method B, Water Vapor Transmission.</li> </ul>
Lightfastness LRV values Fire rating Permeability rating	<ul> <li>and staining the material.</li> <li>Periodic vacuuming is recommended to prevent dust from building up on the materials surface.</li> <li>Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.</li> <li>Testing as per BS 8493:2008+A1:2010, Datacolor DC500.</li> <li>ASTM E84 Class 1 or A and EUROCLASS (B s2 d0).</li> <li>Test result 93.8 as per ASTM E96-12, Method B, Water Vapor Transmission.</li> <li>ASTM D6196, D5197 and D5116, Environmental Chamber Test.</li> </ul>
Lightfastness LRV values Fire rating Permeability rating	<ul> <li>and staining the material.</li> <li>Periodic vacuuming is recommended to prevent dust from building up on the materials surface.</li> <li>Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.</li> <li>Testing as per BS 8493:2008+A1:2010, Datacolor DC500.</li> <li>ASTM E84 Class 1 or A and EUROCLASS (B s2 d0).</li> <li>Test result 93.8 as per ASTM E96-12, Method B, Water Vapor Transmission.</li> <li>ASTM D6196, D5197 and D5116, Environmental Chamber Test.</li> <li>The testing followed UL 2821 "Greenguard Certification Program Method</li> </ul>
Lightfastness LRV values Fire rating Permeability rating Indoor air quality	<ul> <li>and staining the material.</li> <li>Periodic vacuuming is recommended to prevent dust from building up on the materials surface.</li> <li>Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.</li> <li>Testing as per BS 8493:2008+A1:2010, Datacolor DC500.</li> <li>ASTM E84 Class 1 or A and EUROCLASS (B s2 d0).</li> <li>Test result 93.8 as per ASTM E96-12, Method B, Water Vapor Transmission.</li> <li>ASTM D6196, D5197 and D5116, Environmental Chamber Test.</li> <li>The testing followed UL 2821 "Greenguard Certification Program Method for Measuring and Evaluating Chemical Emissions".</li> </ul>

## **Sustainability**

The nonwoven is FSC certified, FSC A000531.

In production, all energy sources are either green, wind or hydro based and all processes are waterbased. The products do not contain PVC, chlorine, plasticizers, heavy metals or harmful dyes.

## Supply and packing

Delivery from stock by the full linear meter or full linear yard.

The average piece length of this quality is approx. 100 linear meter or 110 linear yards. However, as is common within the textile industry, it is not possible to establish a standard roll length. The wallcovering is reeled on to a cardboard core, wrapped in polyethylene and protective end caps are fixed. Each roll is then packed in individual cardboard boxes or tubes, which are also made out of FSC certified woodpulp.

## Harmonized System as per the World Customs Organization and Origin

Textile Wallcovering, paper backed: 5905.00. Made in the Netherlands.



## tapetex wall materials





(440) 248-0000

6655 parkland boulevard solon, ohio 44139 (440) 519-1950 fax www.surfacematerials.com