

# ANASSA™

# de novo® WALL

## Type II

### Physical Properties:

#### Total Weight

#### U.S. Units

#### Metric Units

24.0 oz./LY

744 G/PLM

16 oz./SQ

543 G/PSM

#### Fabric Type

Poly Cotton Osnaburg

#### Material Width

52/54"

132/137 cm

#### Repeat

Horizontal 26" x Vertical 17-1/4"

### Federal Specifications:

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

### Fire Hazard Classification Results:

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 5; Smoke Developed: 15

### Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

MADE IN USA



### Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

### Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.

# de novo® WALL

#### INSTALLATION NOTE

ANASSA™ is a random match / non-reversible pattern  
For specifications and hanging instructions go to:  
[www.surfacematerials.com](http://www.surfacematerials.com)



(440) 248-0000

6655 parkland boulevard  
solon, ohio 44139  
(440) 519-1950 fax  
[www.surfacematerials.com](http://www.surfacematerials.com)

Copyright© 2021. All Rights Reserved  
Any copying or other use is expressly  
prohibited DeNovo Wall is a trademark.

