

Barnaby Gardens™ **de novo**® WALL

Type II

Physical Properties:

Total Weight

U.S. Units

Metric Units

20.0 oz./LY

619 G/PLM

13.3 oz./SQ

451 G/PSM

Fabric Type

Non-Woven

Material Width

52/54"

132/137 cm

Repeat

Horizontal 52" x Vertical 24"

Federal Specifications:

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results:

ASTM E-84 Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 70
Passes NFPA 286 Corner Burn Test

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

MADE IN USA

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

de novo® WALL

INSTALLATION NOTE

Barnaby Gardens™ is a non-reversible match pattern.
For specifications and hanging instructions go to:
www.surfacematerials.com

WBE
Women-Owned Business Enterprise