

# COMMAND<sup>®</sup>

WALLCOVERINGS



## BRUGES LINEN

### Physical Properties

Weight: Type II 20 oz  
Content: 100% Vinyl  
Backing: Osnaburg  
Width: 52/54"  
Repeat: Random Reversible

### Performance:

Fire Rating: Class A, ASTM E84  
Europe CE Fire Tested  
Color Fastness UK Test Result: BS2782-Pass  
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

### Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)  
NSF 342

Product contains up to 40% recycled content  
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA  
Printed with Solvent-Free Inks  
This product has a CE Declaration of of Conformity.

### Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

**Manufactured in the USA**

### Available in 15 Colorways

CM125-2500 Rose	CM125-2508 Dove
CM125-2501 Snow	CM125-2509 Taupe
CM125-2502 Glacier	CM125-2510 Sterling
CM125-2503 Buff	CM125-2511 Stonewash
CM125-2504 Ivory	CM125-2512 Flannel
CM125-2505 Rush	CM125-2513 Greige
CM125-2506 Birlap	CM125-2514 Rust
CM125-2507 Wheat	



**surface**materials

*The ultimate in interior finish products.*

**(440) 248-0000**

6655 parkland boulevard  
solon, ohio 44139  
(440) 519-1950 fax  
[www.surfacematerials.com](http://www.surfacematerials.com)