



Type II

Total Weight U.S. Units **Metric Units Physical Properties:**

> 20.0 oz./LY 619 G/PLM 13.3 oz./SQ 451 G/PSM

Fabric Type Osnaburg

Material Width 52/54" 132/137 cm

Repeat Horizontal 13" x Vertical 6"

Federal Specifications: Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101

Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European

Standard for Decorative Wallcoverings.

Fire Hazard Classification ASTM E-84 Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 45 Results: Passes NFPA 286 Corner Burn Test

Performance Features: Phthalate-free MADE IN USA

· No heavy metals or formaldehyde

Printed with low VOC inks

Five year warranty against materials defects

Environmental Attributes: Ultra-low emitting – Pass rating under CA 01350

NSF/ANSI 342 certified for sustainability

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.



INSTALLATION NOTE

CAPPI™ is a straight match pattern For specifications and hanging instructions go to: www.surfacematerials.com





