

CORCHO™

de novo® WALL

Type II

**Physical Properties:**

	<b>Total Weight</b>	<b>U.S. Units</b>	<b>Metric Units</b>
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg/Polyester	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 36" x Vertical 11.8"	

**Federal Specifications:**

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:**

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 40

**Performance Features:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

MADE IN USA

**Environmental Attributes:**

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

**Permeability, Moisture and Mold:**

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.

de novo® WALL

**INSTALLATION NOTE**  
**CORCHO™** is a random match / reversible pattern  
 For specifications and hanging instructions go to:  
[www.surfacematerials.com](http://www.surfacematerials.com)



**(440) 248-0000**  
 6655 parkland boulevard  
 solon, ohio 44139  
 (440) 519-1950 fax  
[www.surfacematerials.com](http://www.surfacematerials.com)

Copyright© 2021. All Rights Reserved  
 Any copying or other use is expressly  
 prohibited DeNovo Wall is a trademark.

