

---

**WIDTH:** 53"/54" 134/137CM  
**TOTAL WEIGHT:** 32 oz/LY 990.4 G/LM  
**BACKING:** POLY COTTON / OSNABURG

---

ASTM E-84 TUNNEL TEST: **CLASS "A" FIRE RATED**

---

**FEAUTES:** **LOW VOC** **ULTRA-FRESH® ANTIMICROBIAL STAIN RESISTANCE**  
**PHthalate, FORMALDEHYDE AND HEAVY METALS FREE MICROVENTING FOR**  
**PERMEABILITY IS AVAILABLE ON CUSTOM ORDERS ADVANCED WARNING**  
**EFFECT (IONIZATION-TYPE SMOKE DETECTOR) 5 YEAR WARRANTY AGAINST**  
**MATERIAL DEFECTS**

---

**PERMEABILITY:**

VINYL WALLCOVERING CAN ACT AS A VAPOR BARRIER AND CONSEQUENTLY SHOULD NOT BE INSTALLED ON WALLS THAT ARE SUSCEPTIBLE TO EXCESSIVE CONDENSATION OR MOISTURE INFILTRATION. TO REDUCE THE RISK OF FUNGAL GROWTH, IT IS RECOMMENDED THAT ALL WALLCOVERING BE MICRO-VENTED WHEN INSTALLED IN HUMID AND FRINGE ZONE 1 CLIMATES.

---

**PRODUCT SPECIFICATIONS:**

CREATE SURFACE DESIGN WALLCOVERING MEETS OR EXCEEDS ALL REQUIREMENTS OF FEDERAL SPECIFICATION CCCC-W-408A-D, W-101 QUALITY STANDARD FOR POLYMER COATED FABRIC WALLCOVERING AND EN 15102, EUROPEAN STANDARD FOR DECORATIVE WALLCOVERINGS. THIS PRODUCT HAS BEEN ACCEPTED FOR USE BY THE CITY OF NEW YORK DEPT. OF BUILDINGS UNDER MEA-381-93M.



**INSTALLATION NOTE**

**NON-REVERSIBLE / STRAIGHT ACROSS MATCH**

For specifications and hanging instructions go to [surfacematerials.com](http://surfacematerials.com)

Copyright © 2019 Create Wallcoverings  
Any copying or other use is expressly  
prohibited All Rights Reserved  
MADE IN USA