

# INNER REALM™



## Type II

**Physical Properties:**

Total Weight	U.S. Units	Metric Units
	20.0 oz./LY	619 G/PLM
	13.3 oz./SQ	451 G/PSM
Fabric Type	Osnaburg	
Material Width	52/54"	132/137 cm
Repeat	Horizontal 54" x Vertical 24"	

**Federal Specifications:**

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:**

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 20

**Performance Features:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects
- Microventing for permeability is available on a custom order basis

MADE IN USA

**Environmental Attributes:**

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability
- CA Prop 65 compliant

**Permeability, Moisture and Mold:**

Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.



**INSTALLATION NOTE**  
 INNER REALM™ is a random match / reversible pattern  
 For specifications and hanging instructions go to:  
[www.surfacematerials.com](http://www.surfacematerials.com)



**(440) 248-0000**  
 6655 parkland boulevard  
 solon, ohio 44139  
 (440) 519-1950 fax  
[www.surfacematerials.com](http://www.surfacematerials.com)

Copyright© 2021. All Rights Reserved  
 Any copying or other use is expressly  
 prohibited DeNovo Wall is a trademark.

