

JETTATM

Type II

Physical Properties:	Total Weight Fabric Type Material Width Repeat	U.S. Units 28.0 oz./LY 18.6 oz./SQ Poly Cotton Osnaburg 53/54" Horizontal 54" x Vertical 2	Metric Units 619 G/PLM 451 G/PSM 134/137 cm 2-7/8''
Federal Specifications:	Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.		
Fire Hazard Classification Results:	ASTM E-84 Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 15 Passes NFPA 286 Corner Burn Test		
Performance Features:	 Phthalate-free MADE IN USA No heavy metals or formaldehyde Printed with low VOC inks Five year warranty against materials defects Microventing for permeability is available on a custom order basis 		
Environmental Attributes:	 Ultra-low emitting – Pass rating under CA 01350 NSF/ANSI 342 certified for sustainability CA Prop 65 compliant 		
Permeability, Moisture and Mold:	Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.		
	Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free [™] Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.		



INSTALLATION NOTE

JETTA™ is a reversible match pattern For specifications and hanging instructions go to: www.surfacematerials.com





(440) 248-0000 6655 parkland boulevard solon, ohio 44139 (440) 519-1950 fax www.surfacematerials.com Copyright© 2021. All Rights Reserved Any copying or other use is expressly prohibited DeNovo Wall is a trademark.

