

## **KIREINA**<sup>TM</sup>

## Type II

Physical Properties:	<b>Total Weight</b> Fabric Type Material Width Repeat	<b>U.S. Units</b> 24.0 oz./LY 16.0 oz./SQ Non-Woven 52/54" Horizontal 52" x Verti	Metric Units 744 G/PLM 543 G/PSM 132/137 cm cal 24''
Federal Specifications:	Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.		
Fire Hazard Classification Results:	<b>ASTM E-84</b> Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 10 Passes NFPA 286 Corner Burn Test		
Performance Features:	<ul> <li>Phthalate-free MADE II</li> <li>No heavy metals or formaldehyde</li> <li>Printed with low VOC inks</li> <li>Five year warranty against materials defects</li> </ul>		MADE IN USA
Environmental Attributes:	<ul> <li>Ultra-low emitting – Pass rating under CA 01350</li> <li>NSF/ANSI 342 certified for sustainability</li> </ul>		
Permeability, Moisture and Mold:	Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.		



INSTALLATION NOTE

KIREINA<sup>™</sup> is a non-reversible match pattern For specifications and hanging instructions go to: www.surfacematerials.com



Qualified Distributor

SUSTAINABILITY

**STANDARD** 

NSF/ANSI 342



(440) 248-0000 6655 parkland boulevard solon, ohio 44139 (440) 519-1950 fax www.surfacematerials.com Copyright© 2021. All Rights Reserved Any copying or other use is expressly prohibited DeNovo Wall is a trademark.