

# COMMAND<sup>®</sup>

WALLCOVERINGS



## LUMINATA

### Physical Properties

Weight: Type II 20 oz  
Content: 100% Vinyl  
Backing: Non-Woven  
Width: 52/54"  
Repeat: Random Reversible

### Performance:

Fire Rating: Class A, ASTM E84  
Europe CE Fire Tested  
Color Fastness UK Test Result: BS2782-Pass  
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

### Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)  
NSF 342  
Product contains up to 40% recycled content  
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA  
Printed with Solvent-Free Inks  
This product has a CE Declaration of of Conformity.

### Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

### Manufactured in the USA

### Available in 15 Colorways

CM152-2838	CM152-2846
CM152-2839	CM152-2847
CM152-2840	CM152-2848
CM152-2841	CM152-2849
CM152-2842	CM152-2850
CM152-2843	CM152-2851
CM152-2844	CM152-2852
CM152-2845	