## LUSSO



 WIDTH:
 53"/54"
 134/137CM

 TOTAL WEIGHT:
 28 oz/LY
 868 G/LM

 BACKING:
 POLY COTTON / OSNABURG

ASTM E-84 TUNNEL TEST: CLASS "A" FIRE RATED

FEAUTURES: LOW VOC ULTRA-FRESH® ANTIMICROBIAL STAIN RESISTANCE

PHTHALATE, FORMALDEHYDE AND HEAVY METALS FREE MICROVENTING FOR PERMEABILITY IS AVAILABLE ON CUSTOM ORDERS ADVANCED WARNING EFFECT (IONIZATION-TYPE SMOKE DETECTOR) 5 YEAR WARRANTY AGAINST

**MATERIAL DEFECTS** 

## PERMEABILITY:

VINYL WALLCOVERING CAN ACT AS A VAPOR BARRIER AND CONSEQUENTLY SHOULD NOT BE INSTALLED ON WALLS THAT ARE SUSCEPTIBLE TO EXCESSIVE CONDENSATION OR MOISTURE INFILTRATION. TO REDUCE THE RISK OF FUNGAL GROWTH, IT IS RECOMMENDED THAT ALL WALLCOVERING BE MICRO-VENTED WHEN INSTALLED IN HUMID AND FRINGE ZONE 1 CLIMATES.

## **PRODUCT SPECIFICATIONS:**

CREATE SURFACE DESIGN WALLCOVERING MEETS OR EXCEEDS ALL REQUIREMENTS OF FEDERAL SPECIFICATION CCCC-W-408A-D, W-101 QUALITY STANDARD FOR POLYMER COATED FABRIC WALLCOVERING AND EN 15102, EUROPEAN STANDARD FOR DECORATIVE WALLCOVERINGS. THIS PRODUCT HAS BEEN ACCEPTED FOR USE BY THE CITY OF NEW YORK DEPT. OF BUILDINGS UNDER MEA-381-93M.













## **INSTALLATION NOTE**

REVERSE / RANDOM MATCH

For specifications and hanging instructions go to surface materials.com  $\,$ 

> Copyright © 2019 Create Wallcoverings Any copying or other use is expressly prohibited All Rights Reserved MADE IN USA

