

Magnetic Solutions 60"

GLOSS



WWWMS-001

Multi-Functional Performance!

60" Magnet Receptive Dry Erase Wallcovering features a gloss finish, powerful magnet receptive, and a surface made for heavy duty writing.

- Free of PVS, DEHP and PFOA
- Perfect for Curved Walls
- Earth Magnet Friendly
- Easy to Clean
- 10-Year Warranty




surfacematerials

The ultimate in interior finish products.

(440) 248-0000

6655 parkland boulevard
solon, ohio 44139
(440) 519-1950 fax
www.surfacematerials.com



FLOOR TO CEILING



specifications

easy install

WriteMagnetic should be carefully inspected BEFORE CUTTING to confirm that the correct surface and quantity have been ordered and shipped. If you are installing a large order, organize your rolls in sequence before beginning application. Proper surface preparation is critical for a high quality installation. Any imperfections can result in an unappealing finish. Entire wall surface must be smooth and primed with a high-quality, white latex primer.

We suggest hanging the dry erase wallcovering horizontally to eliminate seams in the writing area. For full wall applications, it is recommended a full width strip be centered on the wall in the most likely writing area (see diagram above). Use recommended tools and adhesive for proper installation. After hanging one horizontal strip (a maximum of 20') of dry erase material, examine the installed wallcovering for color uniformity and overall appearance.

accessories

WriteMagnetic is available with a complete line of accessories and optional finishing products. A wide selection of aluminum trims and marker trays offer convenience, cleanliness and aesthetic appeal. A full list of accessories follows in this catalogue. Care and maintenance items will ensure your installation endures everyday use. Choose from recommended markers and writewalls erasers.

warranty

WriteMagnetic is covered by a ten year limited warranty. This warrants that WriteMagnetic will be free from any defects in materials or workmanship and meet the design criteria noted in our specifications when properly applied and installed per our recommended installation instructions.

Product	Roll Size	Width	Backing	Weight	Weight
WWMS-001	50ft	60"	100 % Polyester (2.00 oz/sqyd)	18.30 oz/ sq yd	48 oz/ sq yd
Laminate Thickness	Total Thickness	Tensile Strength	Tear Strength	Flame Resistance	Solvent Resistance
1 mil	30 mils	275 x 208 lbs (ASTM D 5034)	11.8 x 7.2 lbs (ASTM D 2261)	Class A (ASTM E-84)	1,000 Double rubs w/MEK (ASTM D 4752)
Abrasion Resistance	Colorfastness	Magnets			
20,000 Double rubs (ASTM D 3597) Wyzenbeek	Class 4.5 - 5 at 200 AFU (AATCC 16E)	Neodymium Rare Earth Magnets			