


COMMAND[®]

WALLCOVERINGS



MICROFIBER

Physical Properties

Weight: Type II 20 oz
Content: 100% Vinyl
Backing: Osnaburg
Width: 52/54"
Repeat: Random Reversible

Performance:

Fire Rating: Class A, ASTM E84
Europe CE Fire Tested
Color Fastness UK Test Result: BS2782-Pass
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)
NSF 342

Product contains up to 40% recycled content
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA
Printed with Solvent-Free Inks
This product has a CE Declaration of of Conformity.

Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

Manufactured in the USA

Available in 14 Colorways

| | |
|---------------------|-----------------------|
| CM119-2404 Alpine | CM119-2413 Kiwi |
| CM119-2407 Wheat | CM119-2414 Terracotta |
| CM119-2408 Platinum | CM119-2415 Steel |
| CM119-2409 Titanium | CM119-2416 Smoke |
| CM119-2410 Dove | CM119-2417 Denim |
| CM119-2411 Bronze | CM119-2418 Indigo |
| CM119-2412 Pearl | CM119-2419 Plum |