

PETITE RUBIX™



Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 54" x Vertical 18"	

Federal Specifications: Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 20

- Performance Features:**
- Phthalate-free
 - No heavy metals or formaldehyde
 - Printed with low VOC inks
 - Five year warranty against materials defects
 - Microventing for permeability is available on a custom order basis
- MADE IN USA

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
 - NSF/ANSI 342 certified for sustainability
 - CA Prop 65 compliant

Permeability, Moisture and Mold: Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.



INSTALLATION NOTE
PETITE RUBIX™ is a random match / reversible pattern
For specifications and hanging instructions go to:
www.surfacematerials.com



(440) 248-0000
6655 parkland boulevard
solon, ohio 44139
(440) 519-1950 fax
www.surfacematerials.com

Copyright© 2021. All Rights Reserved
Any copying or other use is expressly
prohibited DeNovo Wall is a trademark.

