

POTRERO MAZE™ **de novo**® WALL

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Non-Woven	
	Material	52/54"	132/137 cm
	Width Repeat	Horizontal 26" x Vertical 24"	

Federal Specifications: Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 10 Passes NFPA 286 Corner Burn Test

- Performance Features:**
- Phthalate-free
 - No heavy metals or formaldehyde
 - Printed with low VOC inks
 - Five year warranty against materials defects

Environmental Attributes: • Ultra-low emitting – Pass rating under CA 01350

Permeability, Moisture and Mold: Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.



INSTALLATION NOTE
POTRERO MAZE™ is a non-reversible straight match pattern
 For specifications and hanging instructions go to:
www.surfacematerials.com



(440) 248-0000
 6655 parkland boulevard
 solon, ohio 44139
 (440) 519-1950 fax
www.surfacematerials.com

Copyright© 2023. All Rights Reserved
 Any copying or other use is expressly
 prohibited DeNovo Wall is a trademark.

