

QUADRILLE



WIDTH: 53"/54 134/137CM
TOTAL WEIGHT: 32 oz/LY 990.4 G/LM
BACKING: POLY COTTON / OSNABURG

ASTM E-84 TUNNEL TEST: **CLASS "A" FIRE RATED**

FEAUTES: **LOW VOC** **ULTRA-FRESH® ANTIMICROBIAL STAIN RESISTANCE**
PHthalate, FORMALDEHYDE AND HEAVY METALS FREE MICROVENTING FOR
PERMEABILITY IS AVAILABLE ON CUSTOM ORDERS ADVANCED WARNING
EFFECT (IONIZATION-TYPE SMOKE DETECTOR) 5 YEAR WARRANTY AGAINST
MATERIAL DEFECTS

PERMEABILITY:

VINYL WALLCOVERING CAN ACT AS A VAPOR BARRIER AND CONSEQUENTLY SHOULD NOT BE INSTALLED ON WALLS THAT ARE SUSCEPTIBLE TO EXCESSIVE CONDENSATION OR MOISTURE INFILTRATION. TO REDUCE THE RISK OF FUNGAL GROWTH, IT IS RECOMMENDED THAT ALL WALLCOVERING BE MICRO-VENTED WHEN INSTALLED IN HUMID AND FRINGE ZONE 1 CLIMATES.

PRODUCT SPECIFICATIONS:

CREATE SURFACE DESIGN WALLCOVERING MEET OR EXCEED ALL REQUIREMENTS OF FEDERAL SPECIFICATION CCCC-W-408A-D, W-101 QUALITY STANDARD FOR POLYMER COATED FABRIC WALLCOVERING AND EN 15102, EUROPEAN STANDARD FOR DECORATIVE WALLCOVERINGS. THIS PRODUCT HAS BEEN ACCEPTED FOR USE BY THE CITY OF NEW YORK DEPT. OF BUILDINGS UNDER MEA-381-93M.



INSTALLATION NOTE

NON-REVERSIBLE / STRAIGHT ACROSS MATCH
(CUT LINE SHOULD BE DOWN CENTER OF DIAMOND)

For specifications and hanging instructions go to surfacematerials.com

Copyright © 2019 Create Wallcoverings
Any copying or other use is expressly
prohibited All Rights Reserved
MADE IN USA