



CREATE

WALLCOVERING

SPECIFICATION DATA INFORMATION

PATTERN

Shantung

THICKNESS	.027"
WIDTH	52
HANGING	Random / Reversible
LENGTH	30 Yards per roll
TYPE	II
FEDERAL SPECIFICATION	CCC-W-408A, B, C, D AND ASTM E84
BACKING	Osnaburg/Polyester
TENSILE STRENGTH	50 x 55
TEAR STRENGTH	25 x 25
COLOUR FASTNESS TO LIGHT 200 HOURS	Good
COLD CRACK AT 20F	Satisfactory
TOTAL WEIGHT	20oz
CONSTRUCTION	Fabric backed vinyl wallcovering
DIMENTIONAL STABILITY	Pass
CHEMICAL RESISTANCE	Pass
FLAME SPREAD	Class A index 15
SMOKE DEVELOP	40
SURFACE RESISTANCE	Pass
ABRASION RESISTANCE	Pass
COLOUR FASTNESS	BS2782 – pass*
MEETS CA 01350 VOC REQUIREMNETS	

*UK Test Result



surfacematerials

The ultimate in interior finish products.

(440) 248-0000

6655 parkland boulevard
solon, ohio 44139
(440) 519-1950 fax
www.surfacematerials.com