

# SHIMA TEXTURE™



## Type II

### Physical Properties:

Total Weight	U.S. Units	Metric Units
	20.0 oz./LY	619 G/PLM
	13.3 oz./SQ	451 G/PSM
Fabric Type	Poly Cotton Osnaburg	
Material Width	52/54"	132/137 cm
Repeat	Horizontal 27" x Vertical 24"	

### Federal Specifications:

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

### Fire Hazard Classification Results:

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 10

### Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

MADE IN USA



### Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

### Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.



**INSTALLATION NOTE**

SHIMA TEXTURE™ is a random match / reversible pattern  
For specifications and hanging instructions go to:  
[www.surfacematerials.com](http://www.surfacematerials.com)



**(440) 248-0000**  
6655 parkland boulevard  
solon, ohio 44139  
(440) 519-1950 fax  
[www.surfacematerials.com](http://www.surfacematerials.com)

Copyright© 2021. All Rights Reserved  
Any copying or other use is expressly  
prohibited DeNovo Wall is a trademark.

