



Space Case

Felt Panel Divider

Make a case for your space. Open offices kill productivity — the sights, the sounds, the microwaved salmon — it all has an impact on focus, happiness, and commitment. Space Case is the perfect use-case for two of three sensory improvements: removing distracting noise and views. Dividers big and small can be placed using clamping feet or desktop mounts. It's time for lift-off!

Specifying Acoustics never Felt better.

Bringing our legendary innovation, attention to detail, speed, service, and value to PET felt.

Your Products & Our Purpose

Craft purposeful and beautiful acoustically absorbent products that help designers and builders easily create spaces that enable people to connect and be at their best.



Specifications

Product Name	Space Case
Content	100% Polyester (PET) with a minimum of 60% recycled content
Thickness	12mm
Width	26", 48", 60", or 72"
Height	16"
Weight	.5 lbs/per sq ft
Edge Options	Exposed felt
Sound Performance	ASTM C423-17: NRC = 0.45
Fire Performance	Product made from Class A PET felt material tested under ASTM-84
Variations	Sonus Felt uses an industry standard felting process. Slight and consistent variations in color and "heathering" should be expected when using this sustainable material. Slight imperfections are within normal manufacturing tolerance and not visible in standard installations.
Environmental	Low VOC emissions, formaldehyde and phenol-free. Red List free.
Maintenance	Vacuum to remove any loose dirt or dust. You may use a soft or plastic bristle brush to loosen it. Avoid excess pressure. Compressed air can also be used to dust the material in difficult or large installations. If stains are present, you may saturate a lint-free cloth with a mild detergent or soap and water solution.
Warranty	10 years
Unit of Sale	Per Unit




Hardware



Clamps

C Clamp



surface materials

The ultimate in interior finish products.

(440) 248-0000

6655 parkland boulevard
solon, ohio 44139
(440) 519-1950 fax
www.surfacematerials.com


Colors



Test Results



Absorption Coefficient vs. Freq (Hz)



Freq (Hz)	Absorption Coefficient
160	0.18
250	0.10
500	0.20
800	0.46
1000	0.60
2000	0.90
3150	0.97
NRC	0.45

The Noise Reduction Coefficient (NRC) is calculated as the arithmetic average of the absorption coefficients in the shaded bands only (250, 500, 1250 & 2000 Hz).

ASTM C 423-17