



STYLE:	Tiara II	
STYLE NUMBER:	251CR	
CONSTRUCTION:	Needlebond	
PATTERN:	Single Rib	
FIBER:	PP/ Recycled Polyester Blend	
TOTAL WEIGHT:	30 oz/ly. (20 oz s/y)	
ROLL SIZE:	54" X 24 Lin. yd.	
PACKAGING:	"Crush-Proof" Box	
FLAMMABILITY:	Passes Corner burn NFPA-265; UBC 8-2 TUNNEL TEST, Class A Rating ASTM E-84	
ACOUSTICAL:	ASTM C-423-84A Gypsum Board NRC .20 Acoustic Board NRC .80	
TENSILE STRENGTH: ASTM D-5034, (LBS)	Break L x W 142 x 132	Elongation L x W 195 x 145
TEAR (TRAP) STRENGTH: ASTM D-2261, (LBS)	L x W 30 x 25	
ABRASION RESISTANCE: ASTM D-3884	Rib # cycles 1,720	Rupture # cycles 2,260
COLOR FAST: AATCC-168	Wet Crocking 5	Dry Crocking 5
FMVSS 302:	Passes	
ELECTROSTATIC: AATCC-134	0.2kv	

The above data may change to reflect industry standards. Please verify with manufacturer.