

COMMAND[®]

WALLCOVERINGS



UBERWEAVE

Physical Properties

Weight: Type II 20 oz
Content: 100% Vinyl
Backing: Osnaburg
Width: 52/54"
Repeat: Random Reversible

Performance:

Fire Rating: Class A, ASTM E84
Europe CE Fire Tested
Color Fastness UK Test Result: BS2782-Pass
Meets Federal Specifications CCC-W-408D for scrubbability, washability and stain resistant.

Sustainability:

Low emitting--passes Cal 01350 Standard (Leed EQ 4.2)
NSF 342

Product contains up to 40% recycled content
Free of conflict minerals, heavy metals, solvents, phthalates (BBP, DBP, DEHP, DIDP, DnHP, DnOP), PFC/PFOA
Printed with Solvent-Free Inks
This product has a CE Declaration of of Conformity.

Note:

All wall surfacing materials including wallcoverings, should be selected taking into account the building in which they are to be installed. Buildings that have had liquid or vapor moisture infiltration problems or that have other conditions that make moisture infiltration likely are at risk for mold growth. Should these factors become an issue consult with a professional about the benefits and limitations of wallcovering. All textural type patterns are designed to simulate natural materials. Color, texture and shading should be anticipated as these variations are part of the manufacturing process and add to the richness and beauty of the product.

Manufactured in the USA

Available in 18 Colorways

CM107-2217 Ecrú	CM107-2226 Mocha
CM107-2218 Sand	CM107-2227 Lava
CM107-2219 Ash	CM107-2228 Ember
CM107-2220 Bone	CM107-2229 Slate
CM107-2221 Oyster	CM107-2230 Cadet
CM107-2222 Pumice	CM107-2231 Steel
CM107-2223 Greige	CM107-2232 Spa
CM107-2224 Latte	CM107-2233 Granite
CM107-2225 Stone	CM107-2234 Sunset