recommended **adhesives**

Recommended adhesivea listed below for **LEED contributing points**. Available at your local paint stores.

pigmented wallcovering primer

ECO-988



A pigmented, water-based wallcovering primer - ideal for use in new construction and with permeable or micro-vented wallcoverings. For warranty and best results, use in conjunction with ECO-788 Clay wallcovering adhesives.

- LEED Compliant
- NSF/ANSI 342 Compliant
- Water-resistant for double cutting
- Promotes strippability
- Superior white hiding power

Product code: 11605, 11601

Product C	ode Dry to touch	Base Material	Primer Purpose	Clean Up	Sheen	Paint/Stain Key Features	Indoor/Outdoor
ECO-988	180 min	Water-based	Low Odor, Low-VOC	Soap & Water	Flat/Matte	Mildew Resistant & Mold Resistant	Indoor

clay strippable adhesive

ECO-788



Clay Strippable Adhesive is the second part of a 2-part wall covering primer and adhesive system. For warranty and best results, use in conjunction with ECO-988 pigmented primer.

- LEED Compliant
- NSF/ANSI 342 Compliant
- Strippable with fabric-backed vinyl

Product code: 18605, 18601

Product Cod	e Coverage	Base	VOC (actual/regulatory) Biodegradab	leFlammable	Storage	Indoor/Outdoor
ECO-788	400-450 sq ft per gallon	Clay	0% / 0 g/L as calculated	Yes	Yes	Avoid freezing; keep in cool, dry place	Indoor



LEED COMPLIANT



(440) 248-0000

6655 parkland boulevard solon, ohio 44139 (440) 519-1950 fax www.surfacematerials.com

