

ZETEO™

de novo® WALL

Type II

Physical Properties:

	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg - 10% Recycled Content	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 24" x Vertical 27"	

Federal Specifications:

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results:

ASTM E-84 Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 45

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

MADE IN USA

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

Breathe Free™ Micro-vented wallcovering from DeNovo Wall can be used to help control un-wanted moisture inside a building envelope.

de novo® WALL

INSTALLATION NOTE

ZETEO™ is a random match / reversible pattern
 For specifications and hanging instructions go to:
www.surfacematerials.com



(440) 248-0000
 6655 parkland boulevard
 solon, ohio 44139
 (440) 519-1950 fax
www.surfacematerials.com

Copyright© 2021. All Rights Reserved
 Any copying or other use is expressly
 prohibited DeNovo Wall is a trademark.

